

MODEL	TKF 1350 A TKF 1350 S	TKF 1330 A TKF 1330 S	TKF 1230 A	TAF 1330 A
DRYER TYPE	Heat-Pump	Condenser	Condenser	Vented
CONTROL TYPE	Numerical Display	Numerical Display	LED	Numerical Display
Drying Capacity (kg)	6	6	6	6
Drum	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Drum Volume (lt)	120	120	120	120
Total Power (W)	1200 W	2700 W	2700 W	2700 W
Heating Power (W)	-	2500 W	2500 W	2500 W
220/240 V-50 Hz Connection	•	•	•	•
Amperage (A)	10A	16A/10A - Changeable from 16 A to 10 A	16A/10A - Changeable from 16 A to 10 A	16A/10A - Changeable from 16 A to 10 A
Number of Programmes	14	12	12	12
Automatic Sensor Drying	•	•	•	•
Air Hose supplied (2 meter)	N/A	N/A	N/A	•
Bi-directional drum action	•	•	•	•
Auto anti-creasing	•	•	•	•
Auto cooldown phase	•	•	•	•
Automatic Load Sensing	•	•	•	•
Internal Drum Light	•	•	•	•
Direct drain option	•	•	•	N/A
Adjustable feet	•	•	•	•
Stacking kit	•	•	•	•
CONTROL PANEL				
Time Delay (3-6-9 hour)	•	•	•	-
Time Delay (19 hour)	•	•	-	•
Time to End	•	•	-	•
Programme follower (Drying level display)	Drying Ready to Iron Ready to wear Auto-cooldown End/Anti-Creasing	Drying Ready to Iron Ready to wear Auto-cooldown End/Anti-Creasing	Drying Ready to Iron Ready to wear Auto-cooldown End/Anti-Creasing	Drying Ready to Iron Ready to wear Auto-cooldown End/Anti-Creasing
Child lock	•	•	•	•
Mono Control Jog Dial	•	•	•	•
Soft turn knobs	•	•	•	•
Soft touch buttons	•	•	•	•
INDICATORS				
Fluff/Filter cleaning indicator	•	•	•	•
Water container full indicator	•	•	•	N/A
Condenser/condenser filter cleaning indicator	•	•	•	N/A
End of cycle indicator (Buzzer with cancel feature)	•	•	•	•
DOOR				
Door Opening Angle	150	150	150	150
Door type	Push open	Push open	Push open	Push open
Reversible Door	•	•	•	•
Door Shape	Rectangular	Rectangular	Rectangular	Rectangular
Door Size	39 cm	39 cm	39 cm	39 cm
PERFORMANCE				
Energy Efficiency	A	C	C	C
Energy Consumption (kWh)	2.25	4.05	4.05	3.90
Noise Level (dBA) declaration/measurement	64	64	64	64
Drying Time (min)	140	120	120	103
FUNCTION BUTTONS				
Start/Pause	•	•	•	•
Buzzer with cancel feature	•	•	•	•
DIMENSIONS				
Unpacked (HxWxD) cm	85x60x59,5	85x60x59,5	85x60x59,5	85x60x59,5
Packed (HxWxD) cm	90x70x65	90x70x65	90x70x65	90x70x65

MODEL	TAF 1230 A
DRYER TYPE	Vented
CONTROL TYPE	LED
Drying Capacity (kg)	6
Drum	Stainless Steel
Drum Volume (lt)	120
Total Power (W)	2700 W
Heating Power (W)	2500 W
220/240 V-50 Hz Connection	•
Amperage (A)	16A/10A - Changeable from 16 A to 10 A
Number of Programmes	12
Automatic Sensor Drying	•
Air Hose supplied (2 meter)	•
Bi-directional drum action	•
Auto anti-creasing	•
Auto cooldown phase	•
Automatic Load Sensing	•
Internal Drum Light	•
Direct drain option	N/A
Adjustable feet	•
Stacking kit	•
CONTROL PANEL	
Time Delay (3-6-9 hour)	•
Time Delay (19 hour)	-
Time to End	-
Programme follower (Drying level display)	Drying Ready to Iron Ready to wear Auto-cooldown End/Anti-Creasing
Child lock	•
Mono Control Jog Dial	•
Soft turn knobs	•
Soft touch buttons	•
INDICATORS	
Fluff/Filter cleaning indicator	•
Water container full indicator	N/A
Condenser/condenser filter cleaning indicator	N/A
End of cycle indicator (Buzzer with cancel feature)	•
DOOR	
Door Opening Angle	150
Door type	Push open
Reversible Door	•
Door Shape	Rectangular
Door Size	39 cm
PERFORMANCE	
Energy Efficiency	C
Energy Consumption (kWh)	3.90
Noise Level (dBA) declaration/measurement	64
Drying Time (min)	103
FUNCTION BUTTONS	
Start/Pause	•
Buzzer with cancel feature	•
DIMENSIONS	
Unpacked (HxWxD) cm	85x60x59,5
Packed (HxWxD) cm	90x70x65

MODEL	TKT 5352
DRYER TYPE	Condenser
Front-/Toploader	Top Loader
door reversible	-
FEATURES	
Drying Capacity (kg)	4,5
Electronic control via time delay	•
Electronic control (humidity control)	•
inner drum light	-
Air Hose supplied (2 meter)	-
Bi-directional drum action	•
Auto anti-creasing (end of cycle - 120 min length drum action every 10 min)	•
Auto cooldown phase	•
Direct drain option	-
fluse-filter in the door/drum	-/0
dampness-removal per:	
- condensation	•
cabinet coated steal	•
water collect vessel	•
water-flow through tube	-
CONTROL PANEL	
Display	LED
Remain Time	•
child lock	-
delayed time - option	1-9h
PROGRAMMES	
Number of Programmes	6
cotton	•
easy care	•
wool	•
ventilate/refresh	•
FUNCTION BUTTONS	
Start/Pause	•
Buzzer with cancel feature	•
ELECTRIC SUPPLY	
voltage (V)	230
totally electric supply (kW)	2,5
covering (A)	16
PERFORMANCE	
Energy Efficiency	C
Energy Consumption (kWh)	3,3
Noise Level (dBA) declaration/measurement	
Drying Time (min)	93
DIMENSIONS & WEIGHT	
Unpacked (HxWxD) cm	85x45x60
Packed (HxWxD) cm	90x70x65
Weight (kg) - net	37